# WILSONWERKS ARCHIVES

This camera manual is for reference and historical purposes, all rights reserved.

This cover page is copyrighted material. This document may not be sold or distributed without the express consent of the publisher.

©2008 wilsonwerks Llc

# A SYMBOLIS A PROMISE













The Official Camera of Madison Square Garden







## Canon

11-26, Mrta 3-chome, Minato ku, Tokyo 108, Japan
CANON U.S.A., INC. HARD OFFICE
10 Nevada Drive, Lake Success, Long Island, N.Y. 11042, U.S.A.
CANON U.S.A., INC., MANHATTAN SERVICE STATION
800 Third Avenue, New York, N.Y. 10016, U.S.A.
CANON U.S.A., INC. ATTANTA OFFICE
10 Industrial Drive, Element, Illinois 80126 U.S.A.
CANON U.S.A., INC. CHICAGO OFFICE
140 Industrial Drive, Element, Illinois 80126 U.S.A.
CANON U.S.A., INC. LOS ANGELES OFFICE
127 Paularino Avinue East, Costa Meas, California 92626, U.S.A.
CANON U.S.A., INC. LOS ANGELES SERVICE STATION
1607 West Cell Street, Los Angeles, California 90028 U.S.A.
1607 West Cell Street, Los Angeles, California 90028 U.S.A.
1607 West Cell Street, Los Angeles, California 90028 U.S.A.

CANON U.S.A., INC. SAN FRANCISCO SERVICE STATION 776 Market Street, San Francisco, California 94102, U.S.A.

776 Market Street, San Francisco, California 94102, U.S.A. CANON U.S.A., INC. HAWAII OFFICE Bldg. B.2, 105D Als Moans Blvd., Honolulu, Hawaii 96814, U.S.A. CANON OPTICS & BUSINESS MACHINES CANADA, LTD. HEAD OFFICE

3245 American Drive, Mississauga, Ontario L4V 1N4, Canada CANON OPTICS & BUSINESS MACHINES CANADA, LTD. MONTREAL OFFICE

MONTREAL OFFICE
3070 Brabant-Marineau Street, St. Laurent, Quebec H4S 1K7, Canada
CANON OPTICS & BUSINESS MACHINES CANADA, LTD.
VANCOUVER OFFICE
5800A, No.2 Road, Richmond, B. C. V7C 489, Canada
CANON OPTICS & BUSINESS MACHINES CANADA, LTD.
5020-96 St. Estimonic CENTER
5022-96 St. Estimonic CENTER
5022-96

S222-96 St. Emportor, Ameria 165 549, Canada

CANON AMSTERDAM NV
PO 80x 7907, 1008 AC Amsterdam, The Netherlands
CANON AMSTERDAM NV CAMERA SERVICE CENTER

AND AMSTER

CANON LATIN AMERICA, INC. SALES DEPARTMENT CANON LATIN AMERICA, INC. REPAIR SERVICE CENTER

P.O. Box 2019, Color Free Zone, Hep. Or canaling
CANON HONGKONG TRADING CO., LTD.

CANON HONGKONG TRADING CO., LTD.

CANON AUSTRALIA PTY. LTD.



### **Snap the Happy Times** Day'n' Night







An exceptionally accurate EE mechanism, fully coupled to ASA film speed, programmed shutter speeds and aperture, enables the Canonet 28 to perform perfect exposure metering in daylight. At night, or in dim light, too, the camera's circuitry provides automatic flash control with the Canolite D to extend the ability to obtain perfectly exposed candid shots literally around the clock.

The Canonet 28 has a 40mm lens with 4 elements in 3 groups that assures high resolving power for clearly contrasted images, as well as excellent reproduction of natural colors.

The bright viewfinder with coupled double-image superimposing rangefinder makes focusing extremely easy. It is simply a matter of making the two images become one. It also contains the photographic information you may want to know.

Controls have been simplified for the greatest ease of handling so that, even without the least experience, anyone can take memorable snapshots anywhere.

Weighing only 540 grams, the Canonet 28 is so compact it can be slipped into a pocket or a small handbag for carrying around, always ready to take splendid photographs.

With the Canolite D, flash control is fully automatic, eliminating the need for bothersome calculations. Other flashes can also be used with the Hot Shoe Adapter, by simply turning the aperture ring.

To make sure you don't waste film or miss a shot, the shutter button is automatically locked if shutter speed is not correct or if the subject is too near or too far for good flash snapshots.

For even more versatility, there are various optional accessories besides the Canolite D and the Hot Shoe Adapter, including remote control releases, the Self-Timer 8, Lens Hood 4, and filters.







#### Day and Night EE Exposure Control





If you haven't heard of the Canon Auto Tuning system, the Canonet 28 has it to show you how it provides perfectly automatic flash control when the dark sets in or the light is not enough. The shutter speed, once the Canolite D is mounted, automatically becomes 1/30 sec, and aperture control is also automatic. In daytime, too, the Electric Eye mechanism is fully coupled to film speed, programmed shutter speeds and f/stops.

#### Programmed Electric Eye System

The Canonet 28 is designed to carry out automatically for you those adjustements taking pictures usually requires. Its Programmed Electric Eye System does away with such things as aperture and shutter speed settings. You simply have to focus and shoot for perfectly exposed photographs always. There is nothing else to worry about. And focusing itself couldn't be easier. When the double image in the viewfinder fuses into one, you can press the shutter button and be sure of splendid results. Various accesories available optionally further extend the camera's performance with no difficulty at all.



#### Sharp Canon Lens

For good picture-taking, the lens is all important. The Canon brand underwrites this camera's sharp, quality lens. Its f/2.8 speed, with 4 elements in 3 groups, boasts high resolving power and contrast, as well as vivid reproduction of natural colors over the whole picture area with none of those blurred details that can spoil an otherwise beautiful souvenir.

#### **SPECIFICATIONS**

- ■Type: 35mm leaf shutter type rangefinder camera with Electric Eye
- ■Picture Size: 24 x 36mm
- ■Lens: Canon lens 40mm f/2.8; 4 element, 3 group construction
- •Viewfinder: viewfinder combined with rangefinder, bright frame with parallax correction marks; shutter speed scale and over/under exposure warning marks visible.
- ■EE Mechanism: built-in exposure meter with CdS photocell for fully automatic exposure control; programmed shutter
- ■Exposure Meter Coupling Range: EV8 (f/2.8, 1/30 sec.) to EV17 (f/14.5, 1/620 sec.) with ASA 100 film; Shutter locks outside of coupling range.
- ■Film Speed Scale: ASA 25-400
- **Shutter:** programmed; range: 1/30 sec., f/2.8 to 1/620 sec., f/14.5
- ■Power Source: one 1.35V M20 (#625) mercury battery
- Flash Photography: automatic flash with the Canolite D; Conventional flash photography possible with manual aperture control.
- ■Flash Contact: only direct contact CAT type
- Flash Synchronization: X synchronization at 1/30 sec.
- •Film Loading: easy loading via multislit spool
- Film Advance: by rapid advance lever; single-stroke type; automatic setting to first frame; built-in film transport indicator
- Frame Counter: automatic resetting when camera back is opened
- Film Rewinding: Performed with button on camera bottom and rewind crank.
- ■Filter Size: 48mm
- ■Size: 125 x 75 x 61mm (4-15/16" x 2-15/16" x 2-3/8")
- ■Weight: 540g (1 lb. 3-3/8 ozs.)

Subject to change without notice.

